


PSTricks

3D plots: **pst-3dplot**

A PSTricks package for drawing 3d objects, v2.07a

April 19, 2023



Contents

1 The Parallel projection	5
2 Options	6
3 Coordinates and Axes	6
3.1 Ticks, comma and labels	10
3.2 Offset	13
3.3 Experimental features	14
4 Rotation	19
5 Plane Grids	25
6 Put	27
6.1 \pstThreeDPut	28
6.2 \pstPlanePut	28
7 Nodes	32
8 Dots	32
9 Lines	33
10 Triangles	37
11 Squares	37
12 Boxes	38
13 Ellipses and circles	43
13.1 Options	44
13.2 Ellipse	44
13.3 Circle	45
14 \pstIIIDCylinder	47
15 \psCylinder	50
16 \pstParaboloid	54
17 Spheres	57
18 Mathematical functions	58
18.1 Function $f(x, y)$	58
18.2 Parametric Plots	59
19 Plotting data files	65
19.1 \fileplotThreeD	66
19.2 \dataplotThreeD	66
19.3 \listplotThreeD	66

20 Utility macros	69
20.1 Rotation of three dimensional coordinates	69
20.2 Transformation of coordinates	71
20.3 Adding two vectors	72
20.4 Subtract two vectors	72
21 List of all optional arguments for <code>pst-3dplot</code>	73
References	74

The well known `pstricks` package offers excellent macros to insert more or less complex graphics into a document. `pstricks` itself is the base for several other additional packages, which are mostly named `pst-xxxx`, like `pst-3dplot`. There exist several packages for plotting three dimensional graphical objects. `pst-3dplot` is similiar to the `pst-plot` package for two dimensional objects and mathematical functions.

This version uses the extended keyval package `xkeyval`, so be sure that you have installed this package together with the special one `pst-xkey` for PSTRicks. The `xkeyval` package is available at CTAN:/macros/latex/contrib/xkeyval/. It is also important that after `pst-3dplot` no package is loaded, which uses the old keyval interface.

Thanks for feedback and contributions to:

Bruce Burlton, Bernhard Elsner, Andreas Fehlner, Christophe Jorssen, Markus Krebs, Chris Kuklewicz, Darrell Lamm, Patrice Mégret, Rolf Niepraschk, Michael Sharpe, Uwe Siart, Thorsten Suhling, Maja Zaloznik

1 The Parallel projection

Figure 1 shows a point $P(x, y, z)$ in a three dimensional coordinate system (x, y, z) with a transformation into $P^*(x^*, y^*)$, the Point in the two dimensional system (x_E, y_E) .




Figure 1: Lengths in a three dimensional System

The angle α is the horizontal rotation with positive values for anti clockwise rotations of the 3D coordinates. The angle β is the vertical rotation (orthogonal to the paper plane). In figure 2 we have $\alpha = \beta = 0$. The y -axis comes perpendicular out of the paper plane. Figure 3 shows the same for another angle with a view from the side, where the x -axis shows into the paper plane and the angle β is greater than 0 degrees.




Figure 2: Coordinate System for $\alpha = \beta = 0$ (y -axis comes out of the paper plane)

The two dimensional x coordinate x^* is the difference of the two horizontal lengths $y \cdot \sin \alpha$ und $x \cdot \cos \alpha$ (figure 1):

$$x^* = -x \cdot \cos \alpha + y \cdot \sin \alpha \quad (1)$$

The z-coordinate is unimportant, because the rotation comes out of the paper plane, so we have only a different y^* value for the two dimensional coordinate but no other x^* value. The β angle is well seen in figure 3 which derives from figure 2, if the coordinate system is rotated by 90° horizontally to the left and vertically by β also to the left.

The value of the perpendicular projected z coordinate is $z^* = z \cdot \cos \beta$. With figure 3 we see, that the point $P(x, y, z)$ runs on an elliptical curve when β is constant and α changes continuously. The vertical alteration of P is the difference of the two "perpendicular" lines $y \cdot \cos \alpha$ and $x \cdot \sin \alpha$. These lines are rotated by the angle β , so




Figure 3: Coordinate System for $\alpha = 0$ and $\beta > 0$ (x -axis goes into the paper plane)

we have them to multiply with $\sin \beta$ to get the vertical part. We get the following transformation equations:

$$\begin{aligned} x_E &= -x \cos \alpha + y \sin \alpha \\ y_E &= -(x \sin \alpha + y \cos \alpha) \cdot \sin \beta + z \cos \beta \end{aligned} \quad (2)$$

or written in matrix form:

$$\begin{pmatrix} x_E \\ y_E \end{pmatrix} = \begin{pmatrix} -\cos \alpha & \sin \alpha & 0 \\ -\sin \alpha \sin \beta & -\cos \alpha \sin \beta & \cos \beta \end{pmatrix} \cdot \begin{pmatrix} x \\ y \\ z \end{pmatrix} \quad (3)$$

All following figures show a grid, which has only the sense to make things clearer.

2 Options

All options which are set with `\psset` are global and all which are passed with the optional argument of a macro are local for this macro. This is an important fact for setting the angles `Alpha` and `Beta`. Mostly all macro need these values, this is the reason why they should be set with `\psset` and not part of an optional argument.

3 Coordinates and Axes

`pst-3dplot` accepts cartesian or spherical coordinates. In both cases there must be three parameters: (x, y, z) or alternatively (r, ϕ, θ) , where r is the radius, ϕ the longitude angle and θ the latitude angle. For the spherical coordinates set the option `SphericalCoor=true`. Spherical coordinates are possible for all macros where three dimensional coordinates are expected, except for the plotting functions (math functions and data records). Maybe that this is also interesting for someone, then let me know.

Unlike coordinates in two dimensions, three dimensional coordinates may be specified using PostScript code, which need not be preceded by `!`. For example, assuming `\def\nA{2}, (1,0,2)` and `(90 cos, 100 100 sub, \nA\space 2 div 1 add)` specify the same point. (Recall that a `\space` is required after a macro that will be expanded into PostScript code, as `TEX` absorbs the space following a macro.)

The syntax for drawing the coordinate axes is

```
\pstThreeDCoor [Options]
```


The only special option is `drawing=true|false`, which enables the drawing of the coordinate axes. The default is true. In nearly all cases the `\pstThreeDCoor` macro must be part of any drawing to initialize the 3d-system. If `drawing` is set to `false`, then all ticklines options are also disabled.

Without any options we get the default view with the in table 1 listed options with the predefined values.

Table 1: All new parameters for `pst-3dplot`

name	type	Default	page
Alpha	<angle>	45	8
Beta	<angle>	30	8

name	type	Default	page
xMin	<value>	-1	10
xMax	<value>	4	8
yMin	<value>	-1	10
yMax	<value>	4	8
zMin	<value>	-1	10
zMax	<value>	4	8
nameX	<string>	\$x\$	70
spotX	<angle>	180	70
nameY	<string>	\$y\$	70
spotY	<angle>	0	70
nameZ	<string>	\$z\$	70
spotZ	<angle>	90	70
IIIDticks	false true	false	10
IIIDlabels	false true	false	10
Dx	<value>	1	11
Dy	<value>	1	11
Dz	<value>	1	11
IIIDxTicksPlane	xy xz yz	xy	11
IIIDyTicksPlane	xy xz yz	yz	11
IIIDzTicksPlane	xy xz yz	yz	11
IIIDticksSize	<value>	0.1	10
IIIDxTicksep	<value>	-0.4	11
IIIDyTicksep	<value>	-0.2	11
IIIDzTicksep	<value>	0.2	11
RotX	<angle>	0	19
RotY	<angle>	0	19
RotZ	<angle>	0	19
RotAngle	<angle>	0	21
xRotVec	<angle>	0	21
yRotVec	<angle>	0	21
zRotVec	<angle>	0	21
RotSequence	xyz xzy yxz yzx zxy zyx quaternion	xyz	19
RotSet	set concat keep	set	21
eulerRotation	true false	false	22
IIIDOffset	{<x,y,z>}	{0,0,0}	13
zlabelFactor	<text>	\relax	13
comma	false true	false	11




```
\begin{pspicture}(-3,-2.5)(3,4.25)
 \pstThreeDCoor
\end{pspicture}
```


There are no restrictions for the angles and the max and min values for the axes; all `pstricks` options are possible as well. The following example changes the color and the width of the axes.

The angles Alpha and Beta are important to all macros and should always be set with `psset` to make them global to all other macros. Otherwise they are only local inside the macro to which they are passed.


Alpha is the horizontal and Beta the vertical rotation angle of the Cartesian coordinate system.




```
\begin{pspicture}(-2,-1.25)(1,2.25)
 \pstThreeDCoor[linewidth=1.5pt, linecolor=blue,
 xMax=2, yMax=2, zMax=2,
 Alpha=-60, Beta=30]
\end{pspicture}
```




```
\begin{pspicture}(-2,-2)(2,2)
 \pstThreeDCoor[xMax=2, yMax=2, zMax=2]
\end{pspicture}
```




```
\begin{pspicture}(-2,-2)(2,2)
\pstThreeDCoor[xMax=2,yMax=2,zMax=2,
Alpha=30,Beta=60]
\end{pspicture}
```



```
\begin{pspicture}(-2,-2)(2,2)
\pstThreeDCoor[xMax=2,yMax=2,zMax=2,
Alpha=30,Beta=-60]
\end{pspicture}
```



```
\begin{pspicture}(-2,-2)(2,2)
\pstThreeDCoor[
xMax=2,yMax=2,zMax=2,
Alpha=90,Beta=60]
\end{pspicture}
```




```
\begin{pspicture}(-2,-2)(2,2)
\pstThreeDCoor[linewidth=1.5pt,
xMax=2,yMax=2,zMax=2,
Alpha=40,Beta=0]
\end{pspicture}
```


3.1 Ticks, comma and labels

With the option `IIIDticks` the axes get ticks and with `IIIDlabels` labels. Without ticks also labels are not possible. The optional argument `comma`, which is defined in the package `pst-plot` allows to use a comma instead of a dot for real values. There are several options to place the labels in right plane to get an optimal view. The view of the ticklabels can be changed by redefining the macro


```
\def\psxyzlabel#1{\bgroup\footnotesize\textrm{\tiny #1}\egroup}
```



```
\begin{pspicture}(-3,-2.5)(3,4)
\pstThreeDCoor[IIIDticks,IIIDticksize=0.05]%
\pstThreeDPut(3,0,3){\Huge default}
\end{pspicture}
```




```
\begin{pspicture}(-3,-2.5)(3,4)
\pstThreeDCoor[linecolor=black,
IIIDticks,IIIDlabels,
xMin=-2,yMin=-2,zMin=-2]
\end{pspicture}
```




```
\begin{pspicture}(-3,-2.5)(3,4)
\pstThreeDCoor[linecolor=black,
IIIDticks,IIIDzTicksPlane=yz,
IIIDzTicksep=-0.2,IIIDlabels,
IIIDxTicksPlane=yz,,IIIDxTicksep=-0.2,
IIIDyTicksPlane=xy,,IIIDyTicksep=0.2,
comma,Dx=1.25,Dy=1.5,Dz=0.25]
\end{pspicture}
```


The following example shows a wrong placing of the labels, the planes should be changed.



```
\psset{Alpha=-60,Beta=60}
\begin{pspicture}(-4,-2.25)(1,3)
 \pstThreeDCoor[linecolor=black,%
   IIIDticks,Dx=2,Dy=1,Dz=0.25]%
\end{pspicture}
```




```
\psset{Alpha=-60,Beta=60}
\begin{pspicture}(-4,-2.25)(1,3)
 \pstThreeDCoor[linecolor=black,%
   IIIDticks,IIIDlabels,
   planecorr=normal,
   Dx=2,Dy=1,Dz=0.25]%
\end{pspicture}
```



```
\psset{Alpha=-60,Beta=60}
\begin{pspicture}(-4,-2.25)(1,3)
 \pstThreeDCoor[linecolor=black,%
   IIIDticks,IIIDlabels,
   planecorr=xyrot,
   Dx=2,Dy=1,Dz=0.25]%
\end{pspicture}
```


For the z axis it is possible to define a factor for the values, e.g.



```
\begin{pspicture}(-4,-2.25)(1,4)
 \pstThreeDCoor[IIIDticks,IIIDlabels,
   zlabelFactor=$\cdot10^3$]
\end{pspicture}
```

3.2 Offset

The optional argument `IIIDOffset` allows to set the intermediate point of all axes to another point as the default of $(0,0,0)$. The values have to be put into braces:




```
\begin{pspicture}(-4,-1.25)(1,4)
 \pstThreeDCoor[IIIDticks,IIIDlabels,
 yMin=-3,IIIDOffset={(1,-2,1)}]
\end{pspicture}
```

3.3 Experimental features


All features are as long as they are not really tested called experimental. With the optional argument `coorType`, which is by default 0, one can change the viewing of the axes and all other three dimensional objects.

With `coorType=1` the y-z-axes are orthogonal and the angle between x- and y-axis is `Alpha`. The angle `Beta` is not valid.




```
\psset{coorType=1,Alpha=135}
\begin{pspicture}(-2,-3)(3,3.5)
 \pstThreeDCoor[IIIDticks,zMax=3]%
\end{pspicture}
```

With `coorType=2` the y-z-axes are orthogonal and the angle between x- and y-axis is always 135 degrees and the x-axis is shortened by a factor of $1/\sqrt{2}$. The angle `Alpha` is only valid for placing the ticks, if any. The angle `Beta` is not valid.




```
\psset{coorType=2,Alpha=90,
      IIIDxTicksPlane=yz}
\begin{pspicture}(-2,-2)(3,3.5)
\pstThreeDCoor[IIIDticks,zMax=3]%
\end{pspicture}
```

With `coorType=3` the y–z-axes are orthogonal and the angle between x- and y-axis is always 45 degrees and the x-axis is shortened by a factor of $1/\sqrt{2}$. The angle `Alpha` is only valid for placing the ticks, if any. The angle `Beta` is not valid.




```
\psset{coorType=3,Alpha=90,
      IIIDxTicksPlane=yz}
\begin{pspicture}(-2,-2)(3,3.5)
\pstThreeDCoor[IIIDticks,zMax=3]%
\end{pspicture}
```

`coorType=4` is also called the trimetrie-view. One angle of the axis is 5 and the other 15 degrees. The angles `Alpha` and `Beta` are not valid.




```
\psset{coorType=4,IIIDxTicksPlane=yz}
\begin{pspicture}(-2,-2)(3,3.5)
\pstThreeDCoor[IIIDticks,zMax=3]%
\end{pspicture}
```

With coorType=5 the y - z -axes are orthogonal and the angle between x - and y -axis is variable but should be 30 or 45 degrees and the x -axis is shortened by a factor of 0.5. The angle Beta is not valid.




```
\psset{coorType=5,Alpha=30,
      IIIDxTicksPlane=yz}
\begin{pspicture}(-2,-2)(3,4)
\pstThreeDCoor[IIIDticks,zMax=3]%
\end{pspicture}
```

For coorType=6 the x -axis is shortened by 0.559.



```
\psset{coorType=6}
\begin{pspicture}(-3,-2)(6,6)
\psset{IIIIDxTicksPlane=xz,IIIDyTicksPlane=yz}
\pstThreeDCoor[xMin=0,xMax=5,yMin=0,yMax=5,
zMin=0,zMax=5,IIIDticks,spotX=180,
IIIDlabels=false,linecolor=red]%
\multido{\iA=1+1}{4}{\footnotesize%
\pstThreeDPut(\iA,-0.3,0.1){\iA}%
\pstThreeDPut(-0.3,\iA,0.1){\iA}%
\pstThreeDPut(0,-0.3,\iA){\iA}%
}
\end{pspicture}
```


For coorType=7 the x -axis us shortend by 0.5.




```
\psset{coorType=7}
\begin{pspicture}(-3,-2)(6,6)
\psset{IIIDxTicksPlane=xz,IIIDyTicksPlane=yz}
\pstThreeDCoor[xMin=0,xMax=5,yMin=0,yMax=5,
zMin=0,zMax=5,IIIDticks,spotX=180,
IIIDlabels=false,linecolor=red]%
\multido{\iA=1+1}{4}{\footnotesize%
\pstThreeDPut(\iA,-0.3,0.1){\iA}%
\pstThreeDPut(-0.3,\iA,0.1){\iA}%
\pstThreeDPut(0,-0.3,\iA){\iA}}%
\end{pspicture}
```

4 Rotation


The coordinate system can be rotated independent from the given Alpha and Beta values. This makes it possible to place the axes in any direction and any order. There are the three options RotX, RotY, RotZ and an additional one for the rotating sequence (rotSequence), which can be any combination of the three letters xyz.



```
\begin{pspicture}(-6,-3)(6,3)
\multido{\iA=0+10}{18}{%
  \pstThreeDCoor[RotZ=\iA,xMin=0,xMax=5,yMin=0,yMax=5,zMin=-1,zMax=3]%
}
\end{pspicture}
```




```
\psset{unit=2,linewidth=1.5pt,drawCoor=false}
\begin{pspicture}(-2,-1.5)(2,2.5)%
 \pstThreeDCoor[xMin=0,xMax=2,yMin=0,yMax=2,zMin=0,zMax=2]%
 \pstThreeDBox[RotX=90,RotY=90,RotZ=90,%
  linecolor=red](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotSequence=xzy,RotX=90,RotY=90,RotZ=90,%
  linecolor=yellow](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotSequence=zyx,RotX=90,RotY=90,RotZ=90,%
  linecolor=green](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotSequence=zxy,RotX=90,RotY=90,RotZ=90,%
  linecolor=blue](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotSequence=yxz,RotX=90,RotY=90,RotZ=90,%
  linecolor=cyan](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotSequence=yzx,RotX=90,RotY=90,RotZ=90,%
  linecolor=magenta](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[fillstyle=gradient,RotX=0](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDCoor[xMin=0,xMax=2,yMin=0,yMax=2,zMin=0,zMax=2]%
\end{pspicture}%
```



```
\begin{pspicture}(-2,-1.5)(2,2.5)%
 \pstThreeDCoor[xMin=0,xMax=2,yMin=0,yMax=2,zMin=0,zMax=2]%
 \pstThreeDBox(0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotX=90,linecolor=red](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotX=90,RotY=90,linecolor=green](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
 \pstThreeDBox[RotX=90,RotY=90,RotZ=90,linecolor=blue](0,0,0)(.5,0,0)(0,1,0)(0,0,1.5)
\end{pspicture}%
```

It is sometimes more convenient to rotate the coordinate system by specifying a *single* angle of rotation


`RotAngle` (in degrees) about a vector whose coordinates are `xRotVec`, `yRotVec`, and `zRotVec` using the `quaternion` option for `RotSequence`.



```
\begin{pspicture}(-3,-1.8)(3,3)
\multido{\iA=0+10}{18}{%
\pstThreeDCoor[linecolor=red, RotSequence=quaternion, RotAngle=\iA, xRotVec=3,yRotVec=0,zRotVec=3,
xMin=0,xMax=3, yMin=0,yMax=3, zMin=0,zMax=3]
\pstThreeDCoor[linecolor=blue, RotSequence=quaternion, RotAngle=0, xRotVec=0, yRotVec=0, zRotVec=1,
xMin=0,xMax=3, yMin=0,yMax=3, zMin=0,zMax=3]
\pstThreeDLine[linecolor=blue, linewidth=2pt, arrows=->](0,0,0)(3,0,3)
\uput[0](-2.28,1.2){$\vec{R}_\Phi$}
}
\end{pspicture}
```


Rotations of the coordinate system may be “accumulated” by applying successive rotation sequences using the `RotSet` variable, which is set either as a `pst-3dplot` object’s optional argument, or with a `\psset[pst-3dplot]{RotSet=value}` command. The usual `TEX` scoping rules for the value of `RotSet` hold. The following are valid values of `RotSet`:

- `set`: Sets the rotation matrix using the rotation parameters. This is the default value for `RotSet` and is what is used if `RotSet` is not set as an option for the `pst-3dplot` object, or if not previously set within the object’s scope by a `\psset[pst-3dplot]{RotSet=val}` command.
- `concat`: Concatenates the current rotation matrix with a the new rotation that is defined by the rotation parameters. This option is most useful when multiple `\pstThreeDCoor` calls are made, with or without actual plotting of the axes, to accumulate rotations. A previous value of `RotSet=set` must have been made!
- `keep`: Keeps the current rotation matrix, ignoring the rotation parameters. Mostly used internally to eliminate redundant calculations.




```
\begin{pspicture}(-3,-3)(3.6,3)
\pstThreeDCoor[linecolor=blue, RotSequence=quaternion, RotAngle=0, RotSet=set, xRotVec=0,yRotVec=0,zRotVec=1,
xMin=0,xMax=3, yMin=0, yMax=3, zMin=0, zMax=3]
\pstThreeDCoor[linecolor=green, RotSequence=quaternion, RotSet=concat, RotAngle=22.5, xRotVec=0,yRotVec=0,zRotVec
=1,
xMin=0,xMax=3, yMin=0,yMax=3, zMin=-0.6,zMax=3]
\pstThreeDCoor[linecolor=yellow, RotSequence=quaternion, RotSet=concat, RotAngle=30, xRotVec=0,yRotVec=1,zRotVec
=0,
xMin=0,xMax=3,yMin=-0.6,yMax=3, zMin=0,zMax=3]
\pstThreeDCoor[linecolor=red, RotSequence=quaternion, RotSet=concat, RotAngle=60, xRotVec=1,yRotVec=0,zRotVec=0,
xMin=-0.6,xMax=3, yMin=0,yMax=3, zMin=0,zMax=3]%
\end{pspicture}
```

By default, the rotations defined by `RotX`, `RotY`, and `RotZ` are rotations about the *original* coordinate system's, *x*, *y*, or *z* axes, respectively. More traditionally, however, these rotation angles are defined as rotations about the rotated coordinate system's *current*, *x*, *y*, or *z* axis. The `pst-3dplot` variable option `eulerRotation` can be set to true to activate Euler angle definitions; i.e., `eulerRotation=true`. The default is `eulerRotation=false`.



```
\begin{pspicture}(-4,-5)(6,5)
\pstThreeDCoor[linecolor=red, RotSequence=zyx, RotZ=90,RotY=90,RotX=0,
xMin=0,xMax=5, yMin=0,yMax=5, zMin=0,zMax=5]
\pstThreeDCoor[linecolor=blue, RotSequence=zyx, RotZ=0,RotY=0,RotX=0,
xMin=0,xMax=2.5, yMin=0,yMax=2.5, zMin=0,zMax=2.5]
\end{pspicture}
```



```
\begin{pspicture}(-3,-5)(7,5)
\pstThreeDCoor[eulerRotation=true, linecolor=red, RotSequence=zyx, RotZ=90, RotY=90, RotX=0,
xMin=0,xMax=5, yMin=0,yMax=5, zMin=0,zMax=5]
\pstThreeDCoor[linecolor=blue, RotSequence=zyx, RotZ=0,RotY=0,RotX=0,
xMin=0,xMax=2.5, yMin=0,yMax=2.5, zMin=0,zMax=2.5]
\end{pspicture}
```

5 Plane Grids

```
\pstThreeDPlaneGrid [Options] (xMin,yMin)(xMax,yMax)
```


There are three additional options

planeGrid can be one of the following values: xy, xz, yz. Default is xy.

subticks Number of ticks. Default is 10.¹

planeGridOffset a length for the shift of the grid. Default is 0.


. This macro is a special one for the coordinate system to show the units, but can be used in any way. subticks defines the number of ticklines for both axes and xsubticks and ysubticks for each one.




```
\begin{pspicture}(-4,-3.5)(5,4)
 \pstThreeDCoor[xMin=0,yMin=0,zMin=0,linewidth=2pt]
 \psset{linewidth=0.1pt, linecolor=lightgray}
 \pstThreeDPlaneGrid(0,0)(4,4)
 \pstThreeDPlaneGrid[planeGrid=xz](0,0)(4,4)
 \pstThreeDPlaneGrid[planeGrid=yz](0,0)(4,4)
\end{pspicture}
```

```
\begin{pspicture}(-3,-3.5)(5,4)
 \psset{coorType=2}% set it globally!
 \pstThreeDCoor[xMin=0,yMin=0,zMin=0,linewidth=2pt]
 \psset{linewidth=0.1pt, linecolor=lightgray}
 \pstThreeDPlaneGrid(0,0)(4,4)
 \pstThreeDPlaneGrid[planeGrid=xz](0,0)(4,4)
 \pstThreeDPlaneGrid[planeGrid=yz](0,0)(4,4)
\end{pspicture}
```

¹ This option is also defined in the package *pstricks-add*, so it is necessary to set this option locally or with the family option of *pst-xkey*, eg `\psset[pst-3dplot]{subticks=...}`



```
\begin{pspicture}(-1,-2)(10,10)
\psset{Beta=20,Alpha=160,subticks=7}
\pstThreeDCoor[xMin=0,yMin=0,zMin=0,xMax=7,yMax=7,zMax=7,linewidth=1pt]
\psset{linewidth=0.1pt,linecolor=gray}
\pstThreeDPlaneGrid(0,0)(7,7)
\pstThreeDPlaneGrid[planeGrid=xz,planeGridOffset=7](0,0)(7,7)
\pstThreeDPlaneGrid[planeGrid=yz](0,0)(7,7)
\pscustom[linewidth=0.1pt,fillstyle=gradient,gradbegin=gray,gradmidpoint=0.5,plotstyle=curve]{%
\psset{xPlotpoints=200,yPlotpoints=1}
\psplotThreeD(0,7)(0,0){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\psset{xPlotpoints=1,yPlotpoints=200,drawStyle=yLines}
\psplotThreeD(7,7)(0,7){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\psset{xPlotpoints=200,yPlotpoints=1,drawStyle=xLines}
\psplotThreeD(7,0)(7,0){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\psset{xPlotpoints=1,yPlotpoints=200,drawStyle=yLines}
\psplotThreeD(0,0)(7,0){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\pstThreeDPlaneGrid[planeGrid=yz,planeGridOffset=7](0,0)(7,7)
\end{pspicture}
```



```
\begin{pspicture}(-6,-2)(4,7)
\psset{Beta=10,Alpha=30,subticks=7}
\pstThreeDCoor[xMin=0,yMin=0,zMin=0,xMax=7,yMax=7,zMax=7,linewidth=1.5pt]
\psset{linewidth=0.1pt,linecolor=gray}
\pstThreeDPlaneGrid(0,0)(7,7)
\pstThreeDPlaneGrid[planeGrid=xz](0,0)(7,7)
\pstThreeDPlaneGrid[planeGrid=yz](0,0)(7,7)
\pscustom[linewidth=0.1pt,fillstyle=gradient,gradbegin=gray,gradend=white,gradmidpoint=0.5,
plotstyle=curve]{%
\psset{xPlotpoints=200,yPlotpoints=1}
\psplotThreeD(0,7)(0,0){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\psset{xPlotpoints=1,yPlotpoints=200,drawStyle=yLines}
\psplotThreeD(7,7)(0,7){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\psset{xPlotpoints=200,yPlotpoints=1,drawStyle=xLines}
\psplotThreeD(7,0)(7,7){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\psset{xPlotpoints=1,yPlotpoints=200,drawStyle=yLines}
\psplotThreeD(0,0)(7,0){ x dup mul y dup mul 2 mul add x 6 mul sub y 4 mul sub 3 add 10 div }
\pstThreeDPlaneGrid[planeGrid=xz,planeGridOffset=7](0,0)(7,7)
\pstThreeDPlaneGrid[planeGrid=yz,planeGridOffset=7](0,0)(7,7)
\end{pspicture}
```

The equation for the examples is

$$f(x, y) = \frac{x^2 + 2y^2 - 6x - 4y + 3}{10}$$

6 Put

There exists a special option for the put macros:

`p0origin=lt|lb|t|c|B|b|rt|rB|rb`

for the placing of the text or other objects.




This works only well for the `\pstThreeDPut` macro. The default is `c` and for the `\pstPlanePut` the left baseline `lB`.

6.1 `\pstThreeDPut`

The syntax is similiar to the `\rput` macro:

```
\pstThreeDPut[Options] (x,y,z){any stuff}
```



```
\begin{pspicture}(-2,-1.25)(1,2.25)
\psset{Alpha=-60,Beta=30}
\pstThreeDCoor[linecolor=blue,%
xMin=-1,xMax=2,yMin=-1,yMax=2,zMin=-1,zMax=2]
\pstThreeDPut(1,0.5,1.25){pst-3dplot}
\pstThreeDDot[drawCoor=true](1,0.5,1.25)
\end{pspicture}
```

Internally the `\pstThreeDPut` macro defines the two dimensional node `temp@pstNode` and then uses the default `\rput` macro from `pstricks`. In fact of the perspective view od the coordinate system, the 3D dot must not be seen as the center of the printed stuff.

6.2 `\pstPlanePut`²


The syntax of the `\pstPlanePut` is

```
\pstPlanePut[Options] (x,y,z){Object}
```


We have two special parameters, `plane` and `planecorr`; both are optional. Let's start with the first parameter, `plane`. Possible values for the two dimensional plane are `xy`, `xz`, and `yz`. If this parameter is missing then `plane=xy` is set. The first letter marks the positive direction for the width and the second for the height.

The object can be of any type, in most cases it will be some kind of text. The reference point for the object is the left side and vertically centered, often abbreviated as `lB`. The following examples show for all three planes the same textbox.


² Thanks to Torsten Suhling



```
\begin{pspicture}(-4,-4)(3,4)
\psset{Alpha=30}
\pstThreeDCoor[xMin=-4,yMin=-4,zMin=-4]
\pstPlanePut[plane=xy](0,0,-3){\fbox{\Huge\red xy plane}}
\pstPlanePut[plane=xy](0,0,0){\fbox{\Huge\red xy plane}}
\pstPlanePut[plane=xy](0,0,3){\fbox{\Huge\red xy plane}}
\end{pspicture}
```



```
\begin{pspicture}(-5,-3)(2,3)
\pstThreeDCoor[xMin=2,yMin=-4,zMin=-3,zMax=2]
\pstPlanePut[plane=xz](0,-3,0){\fbox{\Huge\green\textbf{xz plane}}}
\pstPlanePut[plane=xz](0,0,0){\fbox{\Huge\green\textbf{xz plane}}}
\pstPlanePut[plane=xz](0,3,0){\fbox{\Huge\green\textbf{xz plane}}}
\end{pspicture}
```



```
\begin{pspicture}(-2,-4)(6,2)
\pstThreeDCoor[xMin=-4,yMin=-4,zMin=-4,xMax=2,zMax=2]
\pstPlanePut[plane=yz](-3,0,0){\fbox{\Huge\blue\textbf{yz plane}}}
\pstPlanePut[plane=yz](0,0,0){\fbox{\Huge\blue\textbf{yz plane}}}
\pstPlanePut[plane=yz](3,0,0){\fbox{\Huge\blue\textbf{yz plane}}}
\end{pspicture}
```

The following examples use the `p0rigin` option to show that there are still some problems with the `xy`-plane. The second parameter is `planecorr`. As first the values:

`off` Former and default behaviour; nothing will be changed. This value is set, when parameter is missing.


`normal` Default correction, planes will be rotated to be readable.

`xyrot` Additionaly correction for `xy` plane; bottom line of letters will be set parallel to the `y`-axis.

What kind off correction is ment? In the plots above labels for the `xy` plane and the `xz` plane are mirrored. This is not a bug, it's ...mathematics.


`\pstPlanePut` puts the labels on the plane of it's value. That means, `plane=xy` puts the label on the `xy` plane, so that the `x` marks the positive direction for the width, the `y` for the height and the label `XY plane` on the top side of plane. If you see the label mirrored, you just look from the bottom side of plane ...

If you want to keep the labels readable for every view, i. e. for every value of Alpha and Beta, you should set the value of the parameter `planecorr` to `normal`; just like in next example:



```
\begin{pspicture}(-3,-2)(3,4)
\psset{p0Origin=lb}
\pstThreeDCoor[xMax=3.2,yMax=3.2,zMax=4]
\pstThreeDDot[drawCoor=true, linecolor=red](1,-1,2)
\pstPlanePut[plane=xy,planecorr=normal](1,-1,2)
{\fbox{\Huge\red\textbf{XY}}}
\pstThreeDDot[drawCoor=true, linecolor=green](1,3,1)
\pstPlanePut[plane=xz,planecorr=normal](1,3,1)
{\fbox{\Huge\green\textbf{XZ}}}
\pstThreeDDot[drawCoor=true, linecolor=blue](-1.5,0.5,3)
\pstPlanePut[plane=yz,planecorr=normal](-1.5,0.5,3)
{\fbox{\Huge\blue\textbf{YZ}}}
\end{pspicture}
```

But, why we have a third value *xyrot* of *planecorr*? If there isn't an symmetrical view, – just like in this example – it could be usefull to rotate the label for *xy*-plane, so that body line of letters is parallel to the *y* axis. It's done by setting *planecorr=xyrot* :



```
\begin{pspicture}(-2,-2)(4,4)
\psset{p0origin=lb}
\psset{Alpha=69.3,Beta=19.43}
\pstThreeDCoor[xMax=4,yMax=4,zMax=4]
\pstThreeDDot[drawCoor=true,linecolor=red](1,-1,2)
\pstPlanePut[plane=xy,planecorr=xyrot](1,-1,2)
{\fbox{\Huge\red\textbf{XY}}}
\pstThreeDDot[drawCoor=true,linecolor=green](1,3.5,1)
\pstPlanePut[plane=xz,planecorr=xyrot](1,3.5,1)
{\fbox{\Huge\green\textbf{XZ}}}
\pstThreeDDot[drawCoor=true,linecolor=blue](-2,1,3)
\pstPlanePut[plane=yz,planecorr=xyrot](-2,1,3)
{\fbox{\Huge\blue\textbf{YZ}}}
\end{pspicture}
```

7 Nodes

The syntax is

```
\pstThreeDNode(x,y,z){node name}
```


This node is internally a two dimensional node, so it cannot be used as a replacement for the parameters (x, y, z) of a 3D dot, which is possible with the `\psline` macro from `pst-plot`: `\psline{A}{B}`, where A and B are two nodes. It is still on the to do list, that it may also be possible with `pst-3dplot`. On the other hand it is no problem to define two 3D nodes C and D and then drawing a two dimensional line from C to D.

8 Dots

The syntax for a dot is


```
\pstThreeDDot[Options](x,y,z)
```

Dots can be drawn with dashed lines for the three coordinates, when the option `drawCoor` is set to `true`. It is also possible to draw an unseen dot with the option `dotstyle=none`. In this case the macro draws only the coordinates when the `drawCoor` option is set to `true`.



```
\begin{pspicture}(-2,-2)(2,2)
\pstThreeDCoor[xMin=-2,xMax=2,yMin=-2,yMax=2,zMin=-2,zMax=2]
\psset{dotstyle=*,dotscale=2,linecolor=red,drawCoor=true}
\pstThreeDDot(-1,1,1)
\pstThreeDDot(1.5,-1,-1)
\end{pspicture}
```

In the following figure the coordinates of the dots are (a, a, a) where a is $-2, -1, 0, 1, 2$.



```
\begin{pspicture}(-3,-3.25)(2,3.25)
\psset{Alpha=30,Beta=60,dotstyle=square*,dotsize=3pt,%
linecolor=blue,drawCoor=true}
\pstThreeDCoor[xMin=-3,xMax=3,yMin=-3,yMax=3,zMin=-3,zMax=3]
\multido{\n=-2+1}{5}{\pstThreeDDot(\n,\n,\n)}
\end{pspicture}
```


9 Lines

The syntax for a three dimensional line is just like the same from \psline


```
\pstThreeDLine[Options] [<arrow>] (x1,y1,z1) (...) (xn,yn,zn)
```

The option and arrow part are both optional and the number of points is only limited to the memory. All options for lines from pstricks are possible, there are no special ones for a 3D line. There is no difference in drawing a line or a vector; the first one has an arrow of type “-” and the second of “->”.


There is no special polygon macro, because you can get nearly the same with \pstThreeDLine.




```
\begin{pspicture}(-2,-2.25)(2,2.25)
\pstThreeDCoor[xMin=-2,xMax=2,yMin=-2,yMax=2,zMin=-2,zMax=2]
\psset{dotstyle=*,linecolor=red,drawCoor=true}
\pstThreeDDot(-1,1,0.5)
\pstThreeDDot(1.5,-1,-1)
\pstThreeDLine[linewidth=3pt,linecolor=blue,arrows=->]%
(-1,1,0.5)(1.5,-1,-1)
\end{pspicture}
```




```
\begin{pspicture}(-2,-2.25)(2,2.25)
\pstThreeDCoor[xMin=-2,xMax=2,yMin=-2,yMax=2,zMin=-2,zMax=2]
\psset{dotstyle=*,linecolor=red,drawCoor=true}
\pstThreeDDot(-1,1,1)
\pstThreeDDot(1.5,-1,-1)
\pstThreeDLine[linewidth=3pt,linecolor=blue](-1,1,1)(1.5,-1,-1)
\end{pspicture}
```




```
\begin{pspicture}(-2,-2.25)(2,2.25)
\psset{Alpha=30,Beta=60,dotstyle=pentagon*,dotsize=5pt,%
linecolor=red,drawCoor=true}
\pstThreeDCoor[xMin=-2,xMax=2,yMin=-2,yMax=2,zMin=-2,zMax=2]
\pstThreeDDot(-1,1,1)
\pstThreeDDot(1.5,-1,-1)
\pstThreeDLine[linewidth=3pt,linecolor=blue](-1,1,1)(1.5,-1,-1)
\end{pspicture}
```



```
\begin{pspicture}(-2,-2.25)(2,2.25)
\psset{Alpha=30,Beta=-60}
\pstThreeDCoor[xMin=-2,xMax=2,yMin=-2,yMax=2,zMin=-2,zMax=2]
\pstThreeDDot[dotstyle=square,linecolor=blue,drawCoor=true](-1,1,1)
\pstThreeDDot[drawCoor=true](1.5,-1,-1)
\pstThreeDLine[linewidth=3pt,linecolor=blue](-1,1,1)(1.5,-1,-1)
\end{pspicture}
```



```
\begin{pspicture}(-2,-2.25)(2,2.25)
\psset{Alpha=30,Beta=-60}
\pstThreeDCoor[xMin=-2,xMax=2,yMin=-2,yMax=2,zMin=-2,zMax=2]
\pstThreeDDot[dotstyle=square,linecolor=blue,drawCoor=true](-1,1,1)
\pstThreeDDot[drawCoor=true](1.5,-1,-1)
\pstThreeDLine[linewidth=3pt,arrowscale=1.5,%
  linecolor=magenta,linearc=0.5]{<->}{(-1,1,1)}{(1.5,2,-1)}{(1.5,-1,-1)}
\end{pspicture}
```




```
\begin{pspicture}(-3,-2)(4,5)\label{lines}
\pstThreeDCoor[xMin=-3,xMax=3,yMin=-1,yMax=4,zMin=-1,zMax=3]
\multido{\iA=1+1,\iB=60+-10}{5}{%
\ifcase\iA\or\psset{linecolor=red}\or\psset{linecolor=green}%
\or\psset{linecolor=blue}\or\psset{linecolor=cyan}%
\or\psset{linecolor=magenta}%
\fi
\pstThreeDLine[SphericalCoor=true,linewidth=3pt]%
(\iA,0,\iB)(\iA,30,\iB)(\iA,60,\iB)(\iA,90,\iB)(\iA,120,\iB)(\iA,150,\iB)%
(\iA,180,\iB)(\iA,210,\iB)(\iA,240,\iB)(\iA,270,\iB)(\iA,300,\iB)%
(\iA,330,\iB)(\iA,360,\iB)%
}
\multido{\iA=0+30}{12}{%
\pstThreeDLine[SphericalCoor=true,linestyle=dashed]%
(0,0,0)(1,\iA,60)(2,\iA,50)(3,\iA,40)(4,\iA,30)(5,\iA,20)}
\end{pspicture}
```

10 Triangles

A triangle is given with its three points:

```
\pstThreeDTriangle[Options](P1)(P2)(P3)
```

When the option `fillstyle` is set to another value than `none` the triangle is filled with the active color or with the one which is set with the option `fillcolor`.



```
\begin{pspicture}(-3,-4.25)(3,3.25)
\pstThreeDCoor[xMin=-4,xMax=4,yMin=-3,yMax=5,zMin=-4,zMax=3]
\pstThreeDTriangle[drawCoor=true, linecolor=black,%
 linewidth=2pt](3,1,-2)(1,4,-1)(-2,2,0)
\pstThreeDTriangle[fillcolor=yellow, fillstyle=solid,%
 linecolor=blue, linewidth=1.5pt](5,1,2)(3,4,-1)(-1,-2,2)
\end{pspicture}
```

Especially for triangles the option `linejoin` is important. The default value is 1, which gives rounded edges.





Figure 4: The meaning of the option `linejoin=0|1|2` for drawing lines

11 Squares


The syntax for a 3D square is:

```
\pstThreeDSquare[Options](vector o)(vec u)(vec v)
```



```
\begin{pspicture}{-1,-1)(4,3}
\pstThreeDCoor[xMin=-3,xMax=1,yMin=-1,yMax=2,zMin=-1,zMax=3]
\psset{arrows=->,arrowsize=0.2,linecolor=blue,linewidth=1.5pt}
\pstThreeDLine[linecolor=green](0,0,0)(-2,2,3)\uput[45](1.5,1){$\vec{o}$}
\pstThreeDLine(-2,2,3)(2,2,3)\uput[0](3,2){$\vec{u}$}
\pstThreeDLine(-2,2,3)(-2,3,3)\uput[180](1,2){$\vec{v}$}
\end{pspicture}
```

Squares are nothing else than a polygon with the starting point P_o given with the origin vector \vec{o} and the two direction vectors \vec{u} and \vec{v} , which build the sides of the square.




```
\begin{pspicture}{-3,-2)(4,3}
\pstThreeDCoor[xMin=-3,xMax=3,yMin=-1,yMax=4,zMin=-1,zMax=3]
{\psset{fillcolor=blue,fillstyle=solid,drawCoor=true,dotstyle=*}}
\pstThreeDSquare(-2,2,3)(4,0,0)(0,1,0)
\end{pspicture}
```

12 Boxes


A box is a special case of a square and has the syntax

```
\pstThreeDBox[Options] (vector o) (vec u) (vec v) (vec w)
```

These are the origin vector \vec{o} and three direction vectors \vec{u} (x direction), \vec{v} (y direction) and \vec{w} (z direction), which are for example shown in the following figure.



```
\begin{pspicture}(-2,-1.25)(3,4.25)
\psset{Alpha=30,Beta=30}
\pstThreeDCoor[xMin=-3,xMax=1,yMin=-1,yMax=2,zMin=-1,zMax=4]
\pstThreeDDot[drawCoor=true](-1,1,2)
\psset{arrows=->,arrowsize=0.2}
\pstThreeDLine[linecolor=green](0,0,0)(-1,1,2)
\uput[0](0.5,0.5){$\vec{o}$}
\uput[0](0.9,2.25){$\vec{u}$}
\uput[90](0.5,1.25){$\vec{v}$}
\uput[45](2,1.){$\vec{w}$}
\pstThreeDLine[linecolor=blue](-1,1,2)(-1,1,4)
\pstThreeDLine[linecolor=blue](-1,1,2)(1,1,2)
\pstThreeDLine[linecolor=blue](-1,1,2)(-1,2,2)
\end{pspicture}
```




```
\begin{pspicture}(-2,-1.25)(3,4.25)
\psset{Alpha=30,Beta=30}
\pstThreeDCoor[xMin=-3,xMax=1,yMin=-1,yMax=2,zMin=-1,zMax=4]
\pstThreeDBox[hiddenLine](-1,1,2)(2,0,0)(0,1,0)(0,0,2)
\pstThreeDDot[drawCoor=true](-1,1,2)
\end{pspicture}
```


Hidden lines are only possible if you view the object from the front and not from behind.

```
\psBox[Options] (vector o){width}{depth}{height}
```


The origin vector \vec{o} determines the left corner of the box.




```
\begin{pspicture}(-3,-2)(3,5)
\psset{Alpha=2,Beta=10}
\pstThreeDCoor[zMax=5,yMax=7]
\psBox(0,0,0){2}{4}{3}
\end{pspicture}
```




```
\begin{pspicture}(-3,-3)(3,3)
\psset{Beta=50}
\pstThreeDCoor[xMax=3,zMax=6,yMax=6]
\psBox[showInside=false](0,0,0){2}{5}{3}
\end{pspicture}
```




```
\begin{pspicture}(-3,-4)(3,2)
\psset{Beta=40}
\pstThreeDCoor[zMax=3]
\psBox[RotY=20,showInside=false](0,0,0){2}{5}{3}
\end{pspicture}
```




```
\psset{Beta=10,xyzLight=-7 3 4}
\begin{pspicture}(-3,-2)(3,4)
\pstThreeDCoor[zMax=5]
\psBox(0,0,0){2}{5}{3}
\end{pspicture}
```



```
\psset{Beta=10,xyzLight=-7 3 4}
\begin{pspicture}(-3,-2)(3,4)
\psset{Alpha=110}
\pstThreeDCoor[zMax=5]
\psBox(0,0,0){2}{5}{3}
\end{pspicture}
```



```
\psset{Beta=10,xyzLight=-7 3 4}
\begin{pspicture}(-3,-2)(3,3)
\psset{Alpha=200}
\pstThreeDCoor[zMax=3]
\psBox(0,0,0){2}{2}{3}
\end{pspicture}
```



```
\psset{Beta=10,xyzLight=-7 3 4}
\begin{pspicture}(-3,-2)(3,4)
\psset{Alpha=290}
\pstThreeDCoor[zMax=5]
\psBox(0,0,0){2}{5}{3}
\end{pspicture}
```

13 Ellipses and circles

The equation for a two dimensional ellipse (figure 5) is:

$$e : \frac{(x - x_M)^2}{a^2} + \frac{(y - y_M)^2}{b^2} = 1 \quad (4)$$




Figure 5: Definition of an Ellipse

$(x_m; y_m)$ is the center, a and b the semi major and semi minor axes respectively and e the excentricity. For $a = b = 1$ in equation 4 we get the one for the circle, which is nothing else than a special ellipse. The equation written in the parameterform is

$$\begin{aligned} x &= a \cdot \cos \alpha \\ y &= b \cdot \sin \alpha \end{aligned} \quad (5)$$

or the same with vectors to get an ellipse in a 3D system:

$$e : \vec{x} = \vec{m} + \cos \alpha \cdot \vec{u} + \sin \alpha \cdot \vec{v} \quad 0 \leq \alpha \leq 360 \quad (6)$$

where \vec{m} is the center, \vec{u} and \vec{v} the directions vectors which are perpendicular to each other.

13.1 Options

In addition to all possible options from `pst-plot` there are two special options to allow drawing of an arc (with predefined values for a full ellipse/circle):

```
beginAngle=0
endAngle=360
```


Ellipses and circles are drawn with the in section 18.2 described `parametricplotThreeD` macro with a default setting of 50 points for a full ellipse/circle.

13.2 Ellipse


It is very difficult to see in a 3D coordinate system the difference of an ellipse and a circle. Depending to the view point an ellipse maybe seen as a circle and vice versa. The syntax of the ellipse macro is:

```
\pstThreeDEllipse[Options](cx,cy,cz)(ux,uy,uz)(vx,vy,vz)
```

where `c` is for center and `u` and `v` for the two direction vectors. The order of these two vectors is important for the drawing if it is a left or right turn. It follows the right hand rule: flap the first vector \vec{u} on the shortest way into the second one \vec{v} , then you'll get the positive rotating.



```
\begin{pspicture}(-3,-2)(3,3)
\pstThreeDCoor[IIIDticks]
\psset{arrowscale=2,arrows=->}
\pstThreeDLine(0,0,0)(3,0,0)\pstThreeDLine(0,0,0)(0,3,0)\pstThreeDLine(0,0,0)(0,0,3)
\psset{linecolor=blue,linewidth=1.5pt,beginAngle=0,endAngle=90}
\pstThreeDEllipse(0,0,0)(3,0,0)(0,3,0) \pstThreeDEllipse(0,0,0)(0,0,3)(3,0,0)
\pstThreeDEllipse(0,0,0)(0,3,0)(0,0,3)
\end{pspicture}\hspace{2em}
\begin{pspicture}(-3,-2)(3,3)
\pstThreeDCoor[IIIDticks]
\psset{arrowscale=2,arrows=->}
\pstThreeDLine(0,0,0)(3,0,0)\pstThreeDLine(0,0,0)(0,3,0)\pstThreeDLine(0,0,0)(0,0,3)
\psset{linecolor=blue,linewidth=1.5pt,beginAngle=0,endAngle=90}
\pstThreeDEllipse(0,0,0)(0,3,0)(3,0,0) \pstThreeDEllipse(0,0,0)(3,0,0)(0,0,3)
\pstThreeDEllipse(0,0,0)(0,0,3)(0,3,0)
\end{pspicture}
```




```
\begin{pspicture}(-2,-2.25)(2,2.25)
\pstThreeDCoor[xMax=2,yMax=2,zMax=2]
\pstThreeDDot[linecolor=red,drawCoor=true](1,0.5,0.5)
\psset{linecolor=blue, linewidth=1.5pt}
\pstThreeDEllipse(1,0.5,0.5)(-0.5,1,0.5)(1,-0.5,-1)
\psset{beginAngle=0,endAngle=270,linecolor=green}
\pstThreeDEllipse(1,0.5,0.5)(-0.5,0.5,0.5)(0.5,0.5,-1)
\pstThreeDEllipse[RotZ=45,linecolor=red](1,0.5,0.5)(-0.5,0.5,0.5)(0.5,0.5,-1)
\end{pspicture}
```


13.3 Circle

The circle is a special case of an ellipse (equ. 6) with the vectors \vec{u} and \vec{v} which build the circle plain. They must not be orthogonal to each other. The circle macro takes the length of vector \vec{u} into account for the radius. The orthogonal part of vector \vec{v} is calculated internally

```
\pstThreeDCircle[Options] (cx,cy,cz) (ux,uy,uz) (vx,vy,vz)
```



```
\begin{pspicture}(-2,-1.25)(2,2.25)
\pstThreeDCoor[xMax=2,yMax=2,zMax=2, linecolor=black]
\pstThreeDCircle[linestyle=dashed](1,1,0)(1,0,0)(3,4,0)
\pstThreeDCircle[linecolor=blue](1.6,1.6,1.7)(0.8,0.4,0.8)(0.8,-0.8,-0.4)
\pstThreeDDot[drawCoor=true, linecolor=blue](1.6,1.6,1.7)
\psset{linecolor=red, linewidth=2pt, plotpoints=20, showpoints=true}
\pstThreeDCircle(1.6,0.6,1.7)(0.8,0.4,0.8)(0.8,-0.8,-0.4)
\pstThreeDDot[drawCoor=true, linecolor=red](1.6,0.6,1.7)
\end{pspicture}
```



```
\def\radius{4 }\def\PhiI{20 }\def\PhiII{50 }
%
\def\RadIs{\radius \PhiI sin mul}
\def\RadIc{\radius \PhiI cos mul}
\def\RadIIs{\radius \PhiII sin mul}
\def\RadIIC{\radius \PhiII cos mul}
\begin{pspicture}(-4,-4)(4,5)
\psset{Alpha=45,Beta=30,linestyle=dashed}
\pstThreeDCoor[linestyle=solid,xMin=-5,xMax=5,yMax=5,zMax=5,IIIDticks]
\pstThreeDEllipse[linecolor=red](0,0,0)(0,\radius,0)(0,0,\radius)
\pstThreeDEllipse(\RadIs,0,0)(0,\RadIc,0)(0,0,\RadIc)
\pstThreeDEllipse(\RadIIs,0,0)(0,\RadIIC,0)(0,0,\RadIIC)
%
\pstThreeDEllipse[linestyle=dotted,SphericalCoor](0,0,0)(\radius,90,\PhiII)(\radius,0,0)
\pstThreeDEllipse[SphericalCoor,
  beginAngle=-90,endAngle=90](0,0,0)(\radius,90,\PhiII)(\radius,0,0)
\pstThreeDEllipse[linestyle=dotted,SphericalCoor](0,0,0)(\radius,90,\PhiII)(\radius,0,0)
\pstThreeDEllipse[SphericalCoor,
  beginAngle=-90,endAngle=90](0,0,0)(\radius,90,\PhiII)(\radius,0,0)
%
\psset{linecolor=blue,arrows=>,arrowscale=2,linewidth=1.5pt,linestyle=solid}
\pstThreeDEllipse[SphericalCoor,beginAngle=\PhiI,endAngle=\PhiII]%
(0,0,0)(\radius,90,\PhiII)(\radius,0,0)
\pstThreeDEllipse[beginAngle=\PhiII,endAngle=\PhiII](\RadIIs,0,0)(0,\RadIIC,0)(0,0,\RadIIC)
\pstThreeDEllipse[SphericalCoor,beginAngle=\PhiII,endAngle=\PhiII]%
(0,0,0)(\radius,90,\PhiII)(\radius,0,0)
\pstThreeDEllipse[beginAngle=\PhiI,endAngle=\PhiII](\RadIs,0,0)(0,\RadIc,0)(0,0,\RadIc)
\end{pspicture}
\begin{pspicture}(-4,-4)(4,5)

[ ... ]

\pstThreeDEllipse[linestyle=dotted,SphericalCoor](0,0,0)(\radius,90,\PhiII)(\radius,0,0)
\pstThreeDEllipse[SphericalCoor,
  beginAngle=-90,endAngle=90](0,0,0)(\radius,90,\PhiII)(\radius,0,0)
```


```
\pstThreeDEllipse[linestyle=dotted,SphericalCoor](0,0,0)(\radius,90,\PhiIII)(\radius,0,0)
\pstThreeDEllipse[SphericalCoor,
  beginAngle=-90,endAngle=90](0,0,0)(\radius,90,\PhiIII)(\radius,0,0)
%
\pscustom[fillstyle=solid,fillcolor=blue]{
  \pstThreeDEllipse[SphericalCoor,beginAngle=\PhiI,endAngle=\PhiIII]%
  (0,0,0)(\radius,90,\PhiIII)(\radius,0,0)
  \pstThreeDEllipse[beginAngle=\PhiIII,endAngle=\PhiII](\RadIIs,0,0)(0,\RadIIC,0)(0,0,\RadIIC)
  \pstThreeDEllipse[SphericalCoor,beginAngle=\PhiIII,endAngle=\PhiII]%
  (0,0,0)(\radius,90,\PhiIII)(\radius,0,0)
  \pstThreeDEllipse[beginAngle=\PhiI,endAngle=\PhiIII](\RadIs,0,0)(0,\RadIC,0)(0,0,\RadIC)
}
\end{pspicture}
```

14 \pstIIDCylinder


The syntax is

```
\pstIIDCylinder[Options] (x,y,z){radius}{height}
```


(x, y, z) defines the center of the lower part of the cylinder. If it is missing, then $(0, 0, 0)$ are taken into account.




```
\psframebox{%
\begin{pspicture}(-3.5,-2)(3,6)
\pstThreeDCoor[zMax=6]
\pstIIDCylinder{2}{5}
\end{pspicture}
}
```



```
\psframebox{%
\begin{pspicture}(-3.5,-2)(3,6.75)
\pstThreeDCoor[zMax=7]
\pstIIIDCylinder[RotY=30,fillstyle=solid,
  fillcolor=red!20, linecolor=black!60](0,0,0){2}{5}
\end{pspicture}
}
```



```
\psframebox{%
\begin{pspicture}(-3.2,-1.75)(3,6.25)
\pstThreeDCoor[zMax=7]
\pstIIIDCylinder[linecolor=black!20,
    increment=0.4,fillstyle=solid]{2}{5}
\psset{linecolor=red}
\pstThreeDLine{->}(0,0,5)(0,0,7)
\end{pspicture}
}
```




```
\psframebox{%
\begin{pspicture}(-4.5,-1.5)(3,6.8)
\psset{Beta=20}
\pstThreeDCoor[zMax=7]
\pstIIDCylinder[fillcolor=blue!20,
    RotX=45](1,1,0){2}{5}
\end{pspicture}
}
```

15 \psCylinder


The syntax is

```
\psCylinder[Options] (x,y,z){radius}{height}
```


(x,y,z) defines the center of the lower part of the cylinder. If it is missing, then $(0,0,0)$ are taken into account. With `increment` for the angle step and `Hincrement` for the height step, the number of segments can be defined. They are preset to 10 and 0.5.




```
\begin{pspicture}(-3,-2)(3,7)
\psset{Beta=10}
\pstThreeDCoor[zMax=7]
\psCylinder[increment=5]{2}{5}
\end{pspicture}
```




```
\begin{pspicture}(-3,-2)(3,2)
\psset{Beta=10}
\pstThreeDCoor[zMax=1]
\psCylinder[increment=5,Hincrement=0.1]{2}{0.5}
\end{pspicture}
```



```
\begin{pspicture}(-3,-2)(3,6)
\psset{Beta=60}
\pstThreeDCoor[zMax=9]
\psCylinder[RotX=10,increment=5]{3}{5}
\pstThreeDLine[linecolor=red](0,0,0)(0,0,8.5)
\end{pspicture}
```





```
\begin{pspicture}(-3,-2)(3,6)
\psset{Beta=60}
\pstThreeDCoor[zMax=9]
\psCylinder[RotX=10,RotY=45,showInside=false]{2}{5}
\pstThreeDLine[linecolor=red](0,0,0)(0,0,8.5)
\end{pspicture}
```



```
\begin{pspicture}(-3,-2)(3,6)
\psset{Beta=60}
\pstThreeDCoor[zMax=9]
\psCylinder[RotY=-45](0,1,0){2}{5}
\end{pspicture}
```


```
\begin{pspicture}(-2,-1)(2,5)
\pstThreeDCoor[xMax=2,yMax=2,zMin=0,zMax=6,IIIDticks]%
\pstParaboloid{5}{1}% Hoehe 5 und Radius 1
\end{pspicture}
```





```
\begin{pspicture}(0,-3)(7,5)
\pstThreeDCoor[xMax=2,yMax=13,zMin=0,zMax=6,IIIDticks]%
\multido{\rA=2.0+2.5,
\rB=0.15+0.20}{5}{%
\pstParaboloid[% 
SegmentColor={[cmyk]%
{\rB,0.1,0.11,0.1}}]%
(0,\rA,0){5}{1}%
\pstThreeDLine[linestyle=dashed]{->}(0,0,5)(0,13,5)
}
\end{pspicture}
```

17 Spheres




```
\begin{pspicture}(-4,-2.25)(2,4.25)
\pstThreeDCoor[xMin=-3,yMax=2]
\pstThreeDSphere(1,-1,2){2}
\pstThreeDDot[dotstyle=x, linecolor=red, drawCoor=true](1,-1,2)
\end{pspicture}
```

`\pstThreeDSphere[Options] (x,y,z){Radius}`

(x,y,z) is the center of the sphere and possible options are listed in table 3. The segment color must be set as a cmyk color `SegmentColor={[cmyk]{c,m,y,k}}` in parenthesis, otherwise `xcolor` cannot read the values. A white color is given by `SegmentColor={[cmyk]{0,0,0,0}}`.

Table 3: Options for the sphere macro

Option name	value
<code>SegmentColor</code>	cmyk color for the segments (0.2,0.6,1,0)
<code>increment</code>	number for the segments (10)



```
\begin{pspicture}(-4,-2.25)(2,4.25)
\pstThreeDCoor[xMin=-3,yMax=2]
\pstThreeDSphere[SegmentColor={[cmyk]{0,0,0,0}}](1,-1,2){2}
\pstThreeDDot[dotstyle=x,linecolor=red,drawCoor=true](1,-1,2)
\end{pspicture}
```

18 Mathematical functions

There are two macros for plotting mathematical functions, which work similar to the one from `pst-plot`.

18.1 Function $f(x, y)$

The macro for plotting functions does not have the same syntax as the one from `pst-plot` [6], but it is used in the same way:

```
\psplotThreeD[Options] (xMin,xMax) (yMin,yMax) {the function}
```

The function has to be written in PostScript code and the only valid variable names are x and y , f.ex: `{x dup mul y dup mul add` for the math expression $\sqrt{x^2 + y^2}$. The macro has the same plotstyle options as `\psplot`, except the `plotpoints-` option which is split into one for x and one for y (table 4).

The equation 7 is plotted with the following parameters and seen in figure 6.

$$z = 10 \left(x^3 + xy^4 - \frac{x}{5} \right) e^{-(x^2+y^2)} + e^{-((x-1.225)^2+y^2)} \quad (7)$$

The function is calculated within two loops:

```
for (float y=yMin; y<yMax; y+=dy)
    for (float x=xMin; x<xMax; x+=dx)
        z=f(x,y);
```

It depends to the inner loop in which direction the curves are drawn. There are four possible values for the option `drawStyle`:

- `xLines` (default) Curves are drawn in x direction
- `yLines` Curves are drawn in y direction
- `xyLines` Curves are first drawn in x and then in y direction
- `yxLines` Curves are first drawn in y and then in x direction

Table 4: Options for the plot Macros

Option name	value
plotstyle	dots line polygon curve ecurve ccurve none (default)
showpoints	default is false
xPlotpoints	default is 25
yPlotpoints	default is 25
drawStyle	default is xLines yLines xyLines yxLines
hiddenLine	default is false
algebraic	default is false

In fact of the inner loop it is only possible to get a closed curve in the defined direction. For lines in x direction less yPlotpoints are no problem, in difference to xPlotpoints, especially for the plotstyle options line and dots.

Drawing three dimensional functions with curves which are transparent makes it difficult to see if a point is before or behind another one. \psplotThreeD has an option hiddenLine for a primitive hidden line mode, which only works when the y-intervall is defined in a way that $y_2 > y_1$. Then every new curve is plotted over the forgoing one and filled with the color white. Figure 7 is the same as figure 6, only with the option hiddenLine.

```
\begin{pspicture}(-6,-4)(6,5)
\psset{Beta=15}
\psplotThreeD[plotstyle=line,drawStyle=xLines,% is the default anyway
yPlotpoints=50,xPlotpoints=50,linewidth=1pt](-4,4)(-4,4){%
x 3 exp x y 4 exp mul add x 5 div sub 10 mul
2.729 x dup mul y dup mul add neg exp mul
2.729 x 1.225 sub dup mul y dup mul add neg exp add}
\pstThreeDCoor[xMin=-1,xMax=5,yMin=-1,yMax=5,zMin=-1,zMax=5]
\end{pspicture}
```

18.2 Parametric Plots

Parametric plots are only possible for drawing curves or areas. The syntax for this plot macro is:

```
\parametricplotThreeD[Options](t1,t2)(u1,u2){three parametric functions x y z}
```

The only possible variables are t and u with t_1, t_2 and u_1, u_2 as the range for the parameters. The order for the functions is not important and u may be optional when having only a three dimensional curve and not an area.

$$\begin{aligned} x &= f(t, u) \\ y &= g(t, u) \\ z &= h(t, u) \end{aligned} \tag{8}$$




Figure 6: Plot of the equation 7




Figure 7: Plot of the equation 7 with the `hiddenLine=true` option




Figure 8: Plot of the equation 7 with the `drawStyle=yLines` option




Figure 9: Plot of the equation 7 with the `drawStyle=yLines` and `hiddenLine=true` option




Figure 10: Plot of the equation 7 with the `drawStyle=xyLines` option




Figure 11: Plot of the equation 7 with the `drawStyle=xLines` and `hiddenLine=true` option




Figure 12: Plot of the equation 7 with the `drawStyle=yLines` and `hiddenLine=true` option


To draw a spiral we have the parametric functions:

$$\begin{aligned} x &= r \cos t \\ y &= r \sin t \\ z &= t/600 \end{aligned} \tag{9}$$

In the example the t value is divided by 600 for the z coordinate, because we have the values for t in degrees, here with a range of $0^\circ \dots 2160^\circ$. Drawing a curve in a three dimensional coordinate system does only require one parameter, which has to be by default t . In this case we do not need all parameters, so that one can write


```
\parametricplotThreeD[Options](t1,t2){three parametric functions x y z}
```

which is the same as $(0,0)$ for the parameter u .



```
\begin{pspicture}(-3.25,-2.25)(3.25,5.25)
\pstThreeDCoor[zMax=5]
\parametricplotThreeD[xPlotpoints=200,
linecolor=blue,%
linewidth=1.5pt,plotstyle=curve](0,2160){%
2.5 t cos mul 2.5 t sin mul t 600 div}%degrees
\end{pspicture}
```

And the same with the algebraic option:



```
\begin{pspicture}(-3.25,-2.25)(3.25,5.25)
\pstThreeDCoor[zMax=5]
\parametricplotThreeD[xPlotpoints=200,
linecolor=blue,%
linewidth=1.5pt,plotstyle=curve,
algebraic](0,18.86){% radian
2.5*cos(t) | 2.5*sin(t) | t/5.24}
\end{pspicture}
```

Instead of using the `\pstThreeDSphere` macro (see section 17) it is also possible to use parametric functions for a sphere. The macro plots continuous lines only for the t parameter, so a sphere plotted with the longitudes need

the parameter equations as

$$\begin{aligned}x &= \cos t \cdot \sin u \\y &= \cos t \cdot \cos u \\z &= \sin t\end{aligned}\tag{10}$$

The same is possible for a sphere drawn with the latitudes:

$$\begin{aligned}x &= \cos u \cdot \sin t \\y &= \cos u \cdot \cos t \\z &= \sin u\end{aligned}\tag{11}$$

and at last both together is also not a problem when having these parametric functions together in one `pspicture` environment (see figure 13).

```
\begin{pspicture}(-1,-1)(1,1)
\parametricplotThreeD[plotstyle=curve,yPlotpoints=40](0,360)(0,360){%
t cos u sin mul t cos u cos mul t sin
}
\parametricplotThreeD[plotstyle=curve,yPlotpoints=40](0,360)(0,360){%
u cos t sin mul u cos t cos mul u sin
}
\end{pspicture}
```




Figure 13: Different Views of the same Parametric Functions

19 Plotting data files

There are the same conventions for data files which holds 3D coordinates, than for the 2D one. For example:

```
0.0000  1.0000  0.0000
-0.4207  0.9972  0.0191
....
0.0000, 1.0000, 0.0000
-0.4207, 0.9972, 0.0191
....
(0.0000,1.0000,0.0000)
(-0.4207,0.9972,0.0191)
```

....
{0.0000,1.0000,0.0000}
{-0.4207,0.9972,0.0191}
....

There are the same three plot functions:

```
\fileplotThreeD[Options] {<datafile>}
\dataplotThreeD[Options] {data object}
\listplotThreeD[Options] {data object}
```

The in the following examples used data file has 446 entries like

6.26093349..., 2.55876582..., 8.131984...

This may take some time on slow machines when using the \listplotThreeD macro. The possible options for the lines are the ones from table 4.

19.1 \fileplotThreeD

The syntax is very easy

```
\fileplotThreeD[Options] {datafile}
```

If the data file is not in the same directory than the document, insert the file name with the full path. Figure 15 shows a file plot with the option `linestyle=line`.

19.2 \dataplotThreeD

The syntax is

```
\dataplotThreeD[Options] {data object}
```

In difference to the macro \fileplotThreeD the \dataplotThreeD cannot plot any external data without reading this with the macro \readdata which reads external data and save it in a macro, f.ex.: \dataThreeD.[4]

```
\readdata{data object}{datafile}
```


19.3 \listplotThreeD

The syntax is

```
\listplotThreeD[Options] {data object}
```


\listplotThreeD ist similiar to \dataplotThreeD, so it cannot plot any external data in a direct way, too. But \readdata reads external data and saves it in a macro, f.ex.: \dataThreeD.[4] \listplot can handle some additional PostScript code, which can be appended to the data object, f.ex.:

```
\dataread{\data}{data3D.Roessler}
\newcommand{\dataThreeDDraft}{%
\data\space
\gsave % save grafic status
/Helvetica findfont 40 scalefont setfont
45 rotate % rotate 45 degrees
0.9 setgray % 1 ist white
-60 30 moveto (DRAFT) show
\grestore
}
```




```
\begin{pspicture}(-6,-3)(6,10)
\psset{xunit=0.5cm,yunit=0.75cm,Alpha=30,Beta=30}% the global parameters
\pstThreeDCoor[xMin=-10,xMax=10,yMin=-10,yMax=10,zMin=-2,zMax=10]
\fileplotThreeD[plotstyle=line]{data3D.Roessler}
\end{pspicture}%
```

Figure 14: Demonstration of \fileplotThreeD with Alpha=30 and Beta=15



```
\begin{pspicture}(-4.5,-3.5)(4,11)
\psset{xunit=0.5cm,yunit=0.75cm,Alpha=-30}
\pstThreeDCoor[xMin=-10,xMax=10,yMin=-10,yMax=10,zMin=-2,zMax=10]
\dataplotThreeD[plotstyle=line]{\dataThreeD}
\end{pspicture}%
```

Figure 15: Demonstration of \dataplotThreeD with Alpha=-30 and Beta=30



```
\begin{pspicture}(-5,-4)(5,4)
\psset{xunit=0.5cm,yunit=0.5cm,Alpha=0,Beta=90}
\pstThreeDCoor[xMin=-10,xMax=10,yMin=-10,yMax=7.5,zMin=-2,zMax=10]
\listplotThreeD[plotstyle=line]{\dataThreeDDraft}
\end{pspicture}%
```

Figure 16: Demonstration of `\listplotThreeD` with a view from above (`Alpha=0` and `Beta=90`) and some additional PostScript code

Figure 16 shows what happens with this code. For another example see [6], where the macro `\ScalePoints` is modified. This macro is in `pst-3dplot` called `\ScalePointsThreeD`.

20 Utility macros



20.1 Rotation of three dimensional coordinates


With the three optional arguments `RotX`, `RotY` and `RotZ` one can rotate a three dimensional point. This makes only sense when one wants to save the coordinates. In general it is more powerful to use directly the optional parameters `RotX`, `RotY`, `RotZ` for the plot macros. However, the macro syntax is

```
\pstRotPointIIID[RotX=...,RotY=...,RotZ=...](x,y,z)\xVal\yVal\zVal
```

the `\xVal` `\yVal` `\zVal` hold the new rotated coordinates and must be defined by the user like `\def\xVal{}`, where the name of the macro is not important.

The rotation angles are all predefined to 0 degrees.





```
\def\xVal{}\def\yVal{}\def\zVal{}
\begin{pspicture}(-6,-4)(6,5)
 \pstThreeDCoor[xMin=-1,xMax=5,yMin=-1,yMax=5,zMin=-1,zMax=5]
 \multido{\iA=0+10}{36}{\pstRotPointIID[RotX=\iA](2,0,3){\xVal}{\yVal}{\zVal}
   \pstThreeDDot[drawCoor=true](\xVal,\yVal,\zVal)
 }
\end{pspicture}

\begin{pspicture}(-6,-4)(6,5)
 \pstThreeDCoor[xMin=-1,xMax=5,yMin=-1,yMax=5,zMin=-1,zMax=5,
   nameX=u,nameY=v,nameZ=w,spotX=90,spotY=0,spotZ=90]
 \multido{\iA=0+10}{36}{\pstRotPointIID[RotY=\iA](2,0,3){\xVal}{\yVal}{\zVal}
   \pstThreeDDot[drawCoor=true](\xVal,\yVal,\zVal)
 }
\end{pspicture}

\begin{pspicture}(-6,-4)(6,5)
 \pstThreeDCoor[xMin=-1,xMax=5,yMin=-1,yMax=5,zMin=-1,zMax=5]
 \multido{\iA=0+10}{36}{\pstRotPointIID[RotZ=\iA](2,0,3){\xVal}{\yVal}{\zVal}
   \pstThreeDDot[drawCoor=true](\xVal,\yVal,\zVal)
 }
\end{pspicture}
```

20.2 Transformation of coordinates

To run the macros with more than 9 parameters `pst-3dplot` uses the syntax (#1) for a collection of three coordinates (#1,#2,#3). To handle these triplets in PostScript the following macro is used, which converts the parameter #1 into a sequence of the three coordinates, divided by a space. The syntax is:

```
\getThreeDCoor(vector)\macro
```

`\macro` holds the sequence of the three coordinates x y z, divided by a space.

20.3 Adding two vectors

The syntax is

```
\pstaddThreeDVec(vector A) (vector B) \tempa \tempb \tempc
```

\tempa \tempb \tempc must be user or system defined macros, which holds the three coordinates of the vector
 $\vec{C} = \vec{A} + \vec{B}$.

20.4 Subtract two vectors

The syntax is

```
\pstsubThreeDVec(vector A) (vector B) \tempa \tempb \tempc
```

\tempa \tempb \tempc must be user or system defined macros, which holds the three coordinates of the vector
 $\vec{C} = \vec{A} - \vec{B}$.

21 List of all optional arguments for `pst-3dplot`

Key	Type	Default
Debug	boolean	true
alternative	boolean	true
drawing	boolean	true
drawCoor	boolean	true
hiddenLine	boolean	true
SphericalCoor	boolean	true
IIIDshowgrid	boolean	true
CoorCheck	boolean	true
CylindricalCoor	boolean	true
leftHanded	boolean	true
eulerRotation	boolean	true
coorType	ordinary	0
SphericalCoorType	ordinary	0
xMin	ordinary	-1
xMax	ordinary	4
yMin	ordinary	-1
yMax	ordinary	4
zMin	ordinary	-1
zMax	ordinary	4
xThreeDunit	ordinary	1.0
yThreeDunit	ordinary	1.0
zThreeDunit	ordinary	1.0
xRotVec	ordinary	0
yRotVec	ordinary	0
zRotVec	ordinary	0
deltax	ordinary	1.0
deltay	ordinary	1.0
deltaz	ordinary	1.0
Deltax	ordinary	1.0
Deltay	ordinary	1.0
Deltaz	ordinary	1.0
Alpha	ordinary	45
Beta	ordinary	30
RotX	ordinary	0
RotY	ordinary	0
RotZ	ordinary	0
RotAngle	ordinary	0
RotSequence	ordinary	xyz
RotSet	ordinary	set
PlaneSequence	ordinary	
zCoor	ordinary	0
drawStyle	ordinary	xLines
xPlotpoints	ordinary	25
yPlotpoints	ordinary	25
beginAngle	ordinary	0
endAngle	ordinary	360

Continued on next page

Continued from previous page

Key	Type	Default
plane	ordinary	xy
p0rigin	ordinary	c
IIIDdAlpha	ordinary	0
visibleLineStyle	ordinary	solid
invisibleLineStyle	ordinary	dashed
IIIDticks	boolean	true
IIIDlabels	boolean	true
Dz	ordinary	1
IIIDxTicksPlane	ordinary	xy
IIIDyTicksPlane	ordinary	yz
IIIDzTicksPlane	ordinary	yz
IIIDticksize	ordinary	0.1
IIIDxticksep	ordinary	-0.2
IIIDyticksep	ordinary	-0.2
IIIDzticksep	ordinary	0.2
nameX	ordinary	\$x\$
spotX	ordinary	180
nameY	ordinary	\$y\$
spotY	ordinary	0
nameZ	ordinary	\$z\$
spotZ	ordinary	90
planecorr	ordinary	none
planeGrid	ordinary	xy
planeGridOffset	ordinary	0
showInside	boolean	true
SegmentColor	ordinary	[none]
increment	ordinary	10
Hincrement	ordinary	0.5
xyzLight	ordinary	1 1 2
IIIDOffset	ordinary	[none]
zlabelFactor	ordinary	\relax
height	ordinary	5
move	ordinary	0 0
stepFactor	ordinary	0.67

References

- [1] Victor Eijkhout. *T_EX by Topic – A T_EXnician Reference*. 1 **edition**. Heidelberg **and** Berlin: DANTE – lehmanns media, 2014.
- [2] Denis Girou. “Présentation de PSTricks”. in *Cahier GUTenberg*: 16 (**april** 1994), **pages** 21–70.
- [3] Michel Goosens **and others**. *The L_AT_EX Graphics Companion*. second. Boston, Mass.: Addison-Wesley Publishing Company, 2007.
- [4] Laura E. Jackson **and** Herbert Voß. “Die Plot-Funktionen von *psplot*”. in *Die T_EXnische Komödie*: 2/02 (**june** 2002), **pages** 27–34.
- [5] Nikolai G. Kollock. *PostScript richtig eingesetzt: vom Konzept zum praktischen Einsatz*. Vaterstetten: IWT, 1989.

-
- [6] Herbert Voß. “Die mathematischen Funktionen von Postscript”. in *Die TeXnische Komödie*: 1/02 (march 2002), pages 40–47.
 - [7] Herbert Voß. *Presentations with LATEX 2 edition*. Heidelberg and Berlin: DANTE – Lehmanns Media, 2017.
 - [8] Herbert Voß. *PSTricks – Grafik für TeX und LATEX 7 edition*. Heidelberg and Berlin: DANTE – Lehmanns, 2016.
 - [9] Herbert Voß. *PSTricks – Graphics and PostScript for LATEX*. 1 edition. Cambridge – UK: UIT, 2011.
 - [10] Herbert Voß. *LATEX quick reference*. 1 edition. Cambridge – UK: UIT, 2012.
 - [11] Herbert Voss. *PSTricks Support for pdf*. 2002. URL: <http://PSTricks.de/pdf/pdfoutput.phtml>.
 - [12] Michael Wiedmann and Peter Karp. *References for TeX and Friends*. 2003. URL: <http://www.miwie.org/tex-refs/>.
 - [13] Timothy Van Zandt. *multido.tex - a loop macro, that supports fixed-point addition*. 1997. URL: [/macros/eric/multido.tex](http://macros/eric/multido.tex).
 - [14] Timothy Van Zandt and Denis Girou. “Inside PSTricks”. in *TUGboat*: 15 (september 1994), pages 239–246.

Index

Alpha, 6, 8, 14, 15, 30
Beta, 6, 8, 14–16, 30
c, 28
comma, 7, 10
concat, 21
coordinates, 32
coorType, 14–17
\dataplotThreeD, 66
\dataThreeD, 66
dots, 59
dotstyle, 32
drawCoor, 32
drawing, 6
drawStyle, 58
Dx, 7
Dy, 7
Dz, 7

Environment
 pspicture, 65
 eulerRotation, 7, 22

\fileplotThreeD, 66, 67
fillcolor, 37
fillstyle, 37
\getThreeDCoor, 71
hiddenLine, 59
Hincrement, 50
IIIDlabels, 7, 10
IIIDOffset, 7, 13
IIIDticks, 7, 10
IIIDticksize, 7
IIIDxticksep, 7
IIIDxTicksPlane, 7
IIIDyticksep, 7
IIIDyTicksPlane, 7
IIIDzticksep, 7
IIIDzTicksPlane, 7
increment, 50
keep, 21
Keyvalue
 c, 28
 concat, 21
 dots, 59
 increment, 50
 keep, 21
 lB, 28
 line, 59
 none, 37
 normal, 30
 off, 30
 quaternion, 21
 RotSet, 21
 set, 21
 xLines, 58
 xy, 25, 28
 xyLines, 58
 xyrot, 12, 30, 31
 xz, 25, 28
 yLines, 58
 yxLines, 58
 yz, 14, 16, 25, 28

Keyword
 Alpha, 6, 8, 14, 15, 30
 Beta, 6, 8, 14–16, 30
 comma, 7, 10
 coorType, 14–17
 dotstyle, 32
 drawCoor, 32
 drawing, 6
 drawStyle, 58
 Dx, 7
 Dy, 7
 Dz, 7
 eulerRotation, 7, 22
 fillcolor, 37
 fillstyle, 37
 hiddenLine, 59
 Hincrement, 50
 IIIDlabels, 7, 10
 IIIDOffset, 7, 13
 IIIDticks, 7, 10
 IIIDticksize, 7
 IIIDxticksep, 7
 IIIDxTicksPlane, 7
 IIIDyticksep, 7
 IIIDyTicksPlane, 7
 IIIDzticksep, 7
 IIIDzTicksPlane, 7
 linejoin, 37
 linestyle, 66

nameX, 7
 nameY, 7
 nameZ, 7
 plane, 28, 30
 planecorr, 28, 30, 31
 plotpoints, 58
 pOrigin, 27, 30
 RotAngle, 7, 21
 RotSequence, 7, 21
 rotSequence, 19
 RotSet, 7, 21
 RotX, 7, 19, 69
 RotY, 7, 19, 69
 RotZ, 7, 19, 69
 SegmentColor, 57
 SphericalCoor, 6
 spotX, 7
 spotY, 7
 spotZ, 7
 subticks, 25
 xMax, 7
 xMin, 7
 xPlotpoints, 59
 xRotVec, 7, 21
 xscale, 25
 yMax, 7
 yMin, 7
 yPlotpoints, 59
 yRotVec, 7, 21
 yscale, 25
 zlabelFactor, 7, 13
 zMax, 7
 zMin, 7
 zRotVec, 7, 21

latitude angle, 6
 lB, 28
 line, 59, 66
 linejoin, 37
 linestyle, 66
 \listplot, 66
 \listplotThreeD, 66
 longitude angle, 6

Macro
 \dataplotThreeD, 66
 \dataThreeD, 66
 \fileplotThreeD, 66, 67
 \getThreeDCoor, 71
 \listplot, 66
 \listplotThreeD, 66

\parametricplotThreeD, 59, 63
 \psBox, 40
 \psCylinder, 50
 \psline, 32
 \psplot, 58
 \psplotThreeD, 58, 59
 \psset, 6, 25
 \pstaddThreeDVec, 72
 \pstIIDCylinder, 47
 \pstParaboloid, 54
 \pstPlanePut, 28, 30
 \pstRotPointIID, 69
 \pstsubThreeDVec, 72
 \pstThreeDBox, 38
 \pstThreeDCircle, 45
 \pstThreeDCoor, 6, 7, 21
 \pstThreeDDot, 32
 \pstThreeDEllipse, 44
 \pstThreeDLine, 33
 \pstThreeDNode, 32
 \pstThreeDPlaneGrid, 25
 \pstThreeDPut, 10, 28
 \pstThreeDput, 54
 \pstThreeDSphere, 57, 64
 \pstThreeDSquare, 37
 \pstThreeDTriangle, 37
 \readdata, 66
 \rput, 28
 \ScalePoints, 69
 \ScalePointsThreeD, 69
 \space, 6

nameX, 7
 nameY, 7
 nameZ, 7
 none, 32, 37
 normal, 30

off, 30

Package
 pst-3dplot, 4, 6, 21, 32, 69, 71
 pst-plot, 4, 10, 32, 58
 pst-xkey, 4
 pstricks, 4, 28
 xcolor, 54, 57
 xkeyval, 4
 \parametricplotThreeD, 59, 63
 plane, 28, 30
 planecorr, 28, 30, 31
 plotpoints, 58

\psorigin, 27, 30
 \psBox, 40
 \psCylinder, 50
 \psline, 32
 \pspicture, 65
 \psplot, 58
 \psplotThreeD, 58, 59
 \psset, 6, 25
 \pst-3dplot, 4, 6, 21, 32, 69, 71
 \pst-plot, 4, 10, 32, 58
 \pst-xkey, 4
 \pstaddThreeDVec, 72
 \pstIIDCylinder, 47
 \pstParaboloid, 54
 \pstPlanePut, 28, 30
 \pstricks, 4, 28
 \pstRotPOintIID, 69
 \pstsubThreeDVec, 72
 \pstThreeDBox, 38
 \pstThreeDCircle, 45
 \pstThreeDCoor, 6, 7, 21
 \pstThreeDDot, 32
 \pstThreeDEllipse, 44
 \pstThreeDLine, 33
 \pstThreeDNode, 32
 \pstThreeDPlaneGrid, 25
 \pstThreeDPut, 10, 28
 \pstThreeDput, 54
 \pstThreeDSphere, 57, 64
 \pstThreeDSquare, 37
 \pstThreeDTriangle, 37
 quaternion, 21
 \readdata, 66
 RotAngle, 7, 21
 RotSequence, 7, 21
 rotSequence, 19
 RotSet, 7, 21
 RotX, 7, 19, 69
 RotY, 7, 19, 69
 RotZ, 7, 19, 69
 \rput, 28

 \ScalePoints, 69
 \ScalePointsThreeD, 69
 SegmentColor, 57
 set, 21
 \space, 6
 SphericalCoor, 6
 spotX, 7

 spotY, 7
 spotZ, 7
 square, 38
 subticks, 25

 Value
 line, 66
 none, 32
 set, 21
 xy, 28, 30
 xyrot, 31
 vector, 38

 xcolor, 54, 57
 xkeyval, 4
 xLines, 58
 xMax, 7
 xMin, 7
 xPlotpoints, 59
 xRotVec, 7, 21
 xsubticks, 25
 xy, 25, 28, 30
 xyLines, 58
 xyrot, 12, 30, 31
 xz, 25, 28

 yLines, 58
 yMax, 7
 yMin, 7
 yPlotpoints, 59
 yRotVec, 7, 21
 ysubticks, 25
 yxLines, 58
 yz, 14, 16, 25, 28

 zlabelFactor, 7, 13
 zMax, 7
 zMin, 7
 zRotVec, 7, 21